



Dongfeng EQ6752PT Staff Bus Specification

V E H I C L E	Length (mm)	7480	E N G I N E	Model	EQB140-20
	Width (mm)	2360		Manufacturer	Cummins
	Height (mm)	2950, 3160		Position/fuel	Front settled/ diesel
	Inner Height (mm)	1900		Type	In-line, four cylinders, turbocharged, liquid cooling, direct injection
	Wheel base (mm)	3800		Rated output (kw)	103
	Front/rear Overhang (mm)	1280/2400		Max. torque (N.m)	502
	Approaching/Departure angle (mm)	18/12		Displacement (ml)	3900
	One Step Height (mm)	400		Bore × Stroke (mm)	102X120
	G.V.W (kg)	7850		Emission standard	Euro-II
	Seat capacity	30 (29+1)		Volume of rear luggage compartment (m ³)	2.1m ³
Max. speed (km/h)	100				
ITEM		ALLOCATION			
C H A S S I S	Chassis model	EQ6690K2AC1/DF automobile co., Ltd			
	Gear box	DF 145 series gearbox			
	Clutch	Single plate, dried, diaphragm spring, clutch booster			
	Front axle	Dongfeng axle 3T			
	Rear axle	Dongfeng axle 5T			
	Suspension	Steel plate spring, F9 R11			
	Steering	Power steering			
	Brake	Dual circuit full air brake, Energy storage spring brake			
	Oil tank(L)	135L			
	Tires	8.25-16 (Spare tyre is installed in the rear of chassis beam)			
Batteries/Alternator	6-QA-105/70A				
Others	Copper water tank, Air dryer				
B O D Y	Body Structure	None-integral type structure			
	Inner Trimming	Air-conditioner inner trimming, Double inner luggage rack			
	Doors	Pneumatic out-swing door			
	Side windows	Up splice down sliding, light green color			
	Windscreen	Front & Rear : laminated glass & toughened glass			
	Rearview system	Common reversing mirror, Common inner rearview mirror			
	Conditioning	Dongfeng Pa'en inner installed air conditioner (20kw, PN40 Compressor)			
	Heating system	—			
	Defroster	24V, 170W adjustable defroster			
	Audio-visual system	Mp4 HDD player, 17" foldable color LCD			
	Lights	F/R combination lamps, high-mount stop lamp			
	Windscreen wiper	Bi-direction electric rain wiper			
	Hatch door	Steel plate stamping parts (left, right and rear luggage compartment; Air filter and storage battery compartment door; fuel tank door)			
	Passenger Seats	With 2 point retractable type seat belts, 2+2 passenger seats layout, grey color, imitation leather cover, 29 high quality mid-range passenger seats with armrest and adjustable backrest.			
	Paint	Pearl white color metallic paint By advanced Cathode Electrophoresis technology for whole body painting pre-treated, high anti-corrosion and rust protection and chassis anti-corrosion treatment.			
Outer luggage rack	—				
Others	Color-point pattern floor, flat floor with none-sinking rear luggage compartment, half-rolling sunshade curtain, 1 Fire extinguisher (4KG), 2 Safety hammer, whole safety belts, 700 A skylight, Air horn, Electronic clock with temperature display, side window curtains, light yellow color, reversing monitoring system, non-slip mat on driver door step.				

Authorized Distributor:



Express Heavy Equipment Trading & Leasing L.L.C

P O Box: 393763, DIP 1, Dubai-UAE, Phone: +971 4 8855336, Fax: +971 4 8855582
For enquiries please call +971 52 9039729 and write to info@exeuae.com



مواصفات حافلة عمال ماركة دونغ فينغ موديل EQ6752PT

المحرك		المركبة	
20-EQB140	موديل المحرك	7480	الطول الاجمالي (مم)
كميزن	مصنع المحرك	2360	العرض الاجمالي (مم)
امامي / ديزل	الموقع / الوقود	2950, 3160	الارتفاع الاجمالي (مم)
محرك مستقيم . 4 سلندر /	نوع المحرك	1900	الارتفاع من الداخل (مم)
توربو / ميرد		3800	قاعدة العجلات (مم)
103	القوة القصوى (kw)	1280/2400	اليوز - خلفي / امامي (مم)
502	افصى عزم للدوران (Nm/rpm)	Appr18/12	زاوية الانطلاق / الاقتراب
3900	الازاحة (L)	400	G.V.W. (KG)
Euro-II	الانبعاث القياسي	7850	السرعة القصوى (كم / ساعة)
400	ارتفاع اول درج (مم)	30 (29+1)	نسبة الشوط إلى القطر الداخلي (مم)
1+29	عدد الركاب	100	حجم صندوق الامتعة (3م مربع)
المكونات القياسية		المادة	
EQ6690K2AC1 دونغ فينغ موديل		الشاسية	
DF 145 ناقل حركة بدوى 5 سرعات . موديل		علبة الجير	
قايض بصفيحة واحدة		القايض	
دونغ فينغ دانا حمولة 3 طن		المحور الامامي	
دونغ فينغ دانا حمولة 5 طن		المحور الخلفي	
المجموعة كاملة مزود بيسوست ورقية مصممة للحمل و الخدمة الشاقة F9 R11		التعليق	
مقود الى		المقود	
دائرة مزدوجة من فرامل الهواء . فرامل تخزين الزنبرك		الفرامل	
135		خزان الوقود (بالتر)	
8.25-16PR		الاطارات	
6-QA-105/70A		البطارية / المولد	
خزان مياه نحاس . ومجفف الهواء		اخرى	
بناء هيكل شبيه متكامل		بنية الهيكل	
تقليم التكيف الداخلي (تقليم الاجزاء الداخلية من الاسفنج . ارفق مزدوجة للامتعة)		التقليم الداخلي	
باب هوائي امامي دوار وباب طواري خلفي من جهة اليسار		الابواب	
شباك السائق: اطار النيوم منزلق		النوافذ الجانبية	
النوافذ الجانبية: الجانب الاسفل محكم الاغلاق. نوافذ علوية سحابة - لون اخضر فاخ		الارضية	
الامام والخلف : زجاج مغلف مع زجاج مقوى		حاجب الريح	
مرآة يدوية للرؤية الخلفية: مرآة داخلية		نظام الرؤية الخلفية	
مكيف هواء دونغ فينغ (20 KW) . كمبريسور المكيف PN40		مكيف الهواء	
مذيبة الصقيع قابل للتعديل 24V و 170W		مزيل الضباب	
شاشة قابلة للطى ملونة . CD . مشغل راديو HDD MP4		نظام الصوت / الفيديو	
مصابيح حديثة علوية للامام والخلف ومصباح للدرج		واقى الشمس	
ماسحات كهربائية متعكسة		المصابيح	
مقاعد السائق مع ماص للصدمات وحزام امان من 3 مواضع		ماسحة الزجاج	
مقاعد الركاب بلون رمادي خفيف وحزام امان تصميم 2+2		المقاعد	
طلاء ابيض لؤلؤي ميتلاك اللون . بواسطه التكنولوجيا المتقدمة الكاثود الكهربائي لطلاء الهيكل كله مسبق المعالجة . حماية عالية		الصعب	
ضد الصدأ والتآكل ومعالجة ضد التآكل للشاسية		اخرى	
"طفاية حريق (4 كجم) . 2 مطارق امان . ساعة الكترونية مع مؤشر درجة الحرارة . ستارة شمسية قابلة للطى لمستوى النصف .			
أحزمة امان كاملة . ستائر لشباك الجانبى ذات لون اصفر فاخ .			
نظام مراقبة عكسية وحصيرة غيرمنزلفة عند باب السائق ."			

الموزع معتمد بدولة الامارات العربية المتحدة

express

Express Heavy Equipment Trading & Leasing L.L.C

اكسبريس لتجارة و تاجر المعدات الثقيلة ش.ذ.م . صندوق بريدى 393763 دبي . تليفون : +97148855336

للطلبات و الاستفسارات برجاء الاتصال بالحوال الاتى : +971529039729 او ارسال بريد الاكترونى على : info@exeuae.com